

Tel. +49(0)911-642960 Fax. +49(0)911-644456

e-mail info@akemi.de

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PEARL Impregnator

· Article number: 12311, 12312, 12313, 12314
 · UFI: 0NT7-H0AW-V00V-6D8F

1.2 Relevant identified uses of the substance or mixture and

uses advised against

No further relevant information available.

· <u>Application of the substance / the mixture</u>

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Laboratory

Lechstrasse 28 D 90451 Nürnberg

Protective impregnation

D 90451 Nürnbe

· Further information obtainable from:

1.4 Emergency telephone

<u>number:</u> Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· <u>Classification according to Regulation (EC) No 1272/2008</u> Flam. Lig. 3 H226 Flammable liquid and vapour.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aguatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

· Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.

· <u>Storage:</u> Store in a well-ventilated place. Keep cool.

Store locked up.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 Hazard pictograms The product is classified and labelled according to the CLP regulation.



GHS02 GHS08

· Signal word Danger

· Hazard-determining components of

<u>labelling:</u> Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics

Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics

Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics

Hazard statements H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

(Contd. on page 2)



Page 2/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name:	PEARL	Impregnator
-------------	--------------	-------------

(Contd. of page 1)

• Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water. P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

· Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.∨P∨B: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· <u>Description:</u> Mixture: consisting of the following components.

· Dangerous	components:		
	Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics		
	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 EUH066		
	Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics Asp. Tox. 1, H304 EUH066	12.5-25%	
123-86-4	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	<12.5%	
34590-94-8	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<10%	
	Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304 EUH066	<10%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a

doctor.

(Contd. on page 3)



(Contd. of page 2)

Page 3/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed

Headache

Breathing difficulty Profuse sweating

Danger of impaired breathing.

Dizziness Dizziness Nausea

<u>Hazards</u>4.3 Indication of any immediate

medical attention and special

treatment needed

If swallowed, gastric irrigation with added, activated carbon. If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· <u>Suitable extinguishing agents:</u> CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

5.2 Special hazards arising from

the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Page 4/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than

air).

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

<u>storerooms and receptacles:</u> Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

<u>common storage facility:</u> Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

<u>conditions:</u> Store receptacle in a well ventilated area.

Protect from frost.

· Storage class:

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· ingrealents	with limit v	values that	require r	monitoring	at the work	piace:

123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm

34590-94-8 Dipropylene glycol monomethyl ether

IOELV Long-term value: 308 mg/m³, 50 ppm

Skin

· DNELs

123-86-4 n-butyl acetate

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
		6 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	7 mg/kg bw/day (ARB)
		3.4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	600 mg/m³ Air (ARB)
		300 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	48-300 mg/m³ Air (ARB)

34590-94-8 Dipropylene glycol monomethyl ether

Oral DNEL (Langzeit-wiederholt) 1.67 mg/kg bw/day (BEV)

(Contd. on page 5)



Page 5/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 4)

			(Conta. or	page +)	ř
Dermal	DNEL (Langzeit-wiederholt)	65 mg/kg bw/day (ARB)			I
		15 mg/kg bw/day (BEV)			١
Inhalative	DNEL (Langzeit-wiederholt)	310 mg/m³ Air (ARB)			ı
		37.2 mg/m³ Air (BEV)			

· PNECs

123-86-4 n-butyl acetate

PNEC (wässrig) 35.6 mg/l (KA) 0.018 mg/l (MW) 0.18 mg/l (SW) 0.36 mg/l (WAS)

PNEC (fest) 0.0903 mg/kg Trockengew (BO) 0.0981 mg/kg Trockengew (MWS) 0.981 mg/kg Trockengew (SWS)

34590-94-8 Dipropylene glycol monomethyl ether

PNEC (wässrig) 4,168 mg/l (KA) 1.9 mg/l (SW)

PNEC (fest)

19 mg/l (SW)

2.74 mg/kg Trockengew (BO)

7.02 mg/kg Trockengew (MWS)

70.2 mg/kg Trockengew (SWS)

Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic

measures: Do not eat, drink, smoke or sniff while working.

Apply solvent resistant skin cream before starting work.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection: Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

• <u>Hand protection</u> Preventive skin protection by use of skin-protecting agents is recon After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of

protective gloves:

STOKODERM (http://www.stoko.com)

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves: STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (http://www.stoko.com)

Skin protection agent recommendation for skin aftercare:



(Contd. on page 6)



Page 6/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).

· Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6; 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are

suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890)

Butyl rubber, BR

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Chloroprene rubber, CR

Camapren (KCL, Art_No. 720, 722, 726)

Butoject (KCL, Art_No. 897, 898)
Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
Butoject (KCL, Art_No. 897, 898)

Butyl rubber, BR

Not suitable are gloves made of the following materials:

Natural rubber, NR Leather gloves

Strong material gloves

· Eye/face protection Goggles recommended during refilling

· Body protection: Protective work clothing

(Contd. on page 7)



Page 7/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 6)

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless Specific type · Odour:

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range Undetermined. · Flammability Not applicable.

· Lower and upper explosion limit

0.7 Vol % · Lower: · Upper: 10.4 Vol % · Flash point: 56 °C

· Decomposition temperature: Not determined. · pH Not determined. Not applicable

· Viscosity:

· Kinematic viscosity Not determined. Not determined. · Dynamic:

· Solubility

Not miscible or difficult to mix. · water:

Not determined. Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure:

· Density and/or relative density

Density at 20 °C: 0.82 g/cm³ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

Product is not selfigniting. Auto-ignition temperature:

Product does not present an explosion hazard. Explosive properties:

· Solvent content:

90.0 % Organic solvents: · Solids content: 0.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives

Void

· Flammable gases

Void

· Aerosols

Void

· Oxidising gases

Void

· Gases under pressure

Void

(Contd. on page 8)



Page 8/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator (Contd. of page 7) · Flammable liquids Flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Organic peroxides Void · Corrosive to metals Void · Desensitised explosives

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

Void

10.2 Chemical stability
 Thermal decomposition /

conditions to be avoided:

10.3 Possibility of hazardous

reactions

· 10.4 Conditions to avoid

10.5 Incompatible materials:

· 10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

Reacts with strong oxidising agents. Forms flammable gases/fumes.

No further relevant information available. No further relevant information available.

Carbon monoxide and carbon dioxide

(Contd. on page 9)



Page 9/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 8)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxi	city	Based on available data, the classification criteria are not met.			
· LD/LC50 v	· LD/LC50 values relevant for classification:				
Hydrocar	bons, C11-C12,	Isoalkanes, <2% aromatics			
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rabbit)			
Hydrocar	bons, C11-C13,	Isoalkanes, <2% aromatics			
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rabbit)			
	LD50	>5,000 mg/kg (rabbit)			
Inhalative	LC50/4h	2.5 mg/m3 (rat)			
	LC50/8h	>5,000 ppm (rat)			
	NOAEC	1,000 mg/l (rat)			
123-86-4	123-86-4 n-butyl acetate				
Oral	LD50	10,760 mg/kg (rat) (OECD 423)			
Dermal	LD50	>14,112 mg/kg (rabbit) (OECD 402)			
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)			
	LC50 390 mg/m3 (rat)				
LC50/48h 64 mg/l (Brachydanio rerio)					
34590-94-8 Dipropylene glycol monomethyl ether					
Oral	LD50	5,383 mg/kg (rat)			
	NOAEL	5,000 mg/kg (rat)			
Dermal	LD50	5,001 mg/kg (rabbit)			
		9,500 mg/kg (rat)			
NOEL 2,850 mg/kg (rabbit)		2,850 mg/kg (rabbit)			
Inhalative LC50/4 h 3,080 mg/l (rat)		- , ,			
Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics					
Oral	LD50	>5,000 mg/kg (rat)			
		>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rabbit)			
Inhalative	NOAEL	>10,400 mg/m³ (rat)			

innaiative	NOAEL	>10,400	mg/m² (rai)
	sion/irritation		Based on available data, the classification criteria are not met.
 Serious ey 	∕e damage/irrita	tion	Based on available data, the classification criteria are not met.
Respirator	y or skin sensiti	sation	Based on available data, the classification criteria are not met.
Germ cell	mutagenicity		Based on available data, the classification criteria are not met.
· Carcinoge	nicity		Based on available data, the classification criteria are not met.
Reproduct	ive toxicity		Based on available data, the classification criteria are not met.
· STOT-sing	gle exposure		Based on available data, the classification criteria are not met.
STOT-repo	eated exposure		Based on available data, the classification criteria are not met.
- Aspiration	hazard		May be fatal if swallowed and enters airways.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 10)



Page 10/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 9)

SECTION 12: Ecological information			
· 12.1 Toxicity	Y.		
· Aquatic toxic	ity:		
Hydrocarbo	ns, C11-C12, Isoalkanes, <2% aromatics		
EL0/48h	1,000 mg/l (daphnia magna)		
EL0/72h	1,000 mg/l (Pseudokirchneriella subcapitata)		
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)		
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata)		
NOEC/21d	0.011 mg/l (daphnia magna)		
NOELR/21d	1 mg/l (daphnia magna)		
Hydrocarbo	ns, C11-C13, Isoalkanes, <2% aromatics		
EC50/48h	>1,000 mg/l (daphnia magna)		
ErC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)		
EL0/48h	1,000 mg/l (daphnia magna)		
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)		
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata)		
NOELR/21d	1 mg/l (daphnia magna)		
EC50/72h	>1,000 mg/l (green alge)		
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss)		
123-86-4 n-b	n-butyl acetate		
EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)		
EC50/96h	320 mg/l (green alge)		
LC50/24h	205 mg/l (daphnia magna)		
IC50/72h	648 mg/l (Desmodesmus subspicatus)		
EC10/18h	959 mg/l (pseudomonas putida)		
EC50/48h	44 mg/l (daphnia magna)		
EC50/16h	959 mg/l (pseudomonas putida)		
NOEC	200 mg/kg (Desmodesmus subspicatus)		
NOEC/21d	23 mg/l (daphnia magna)		
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)		
	674 mg/l (Scenedesmus subspicatus)		
LC50/96h	62 mg/l (Danio rerio.)		
	81 mg/l (piscis)		
	100 mg/l (lepomis macrochirus)		
	62 mg/l (Leuciscus idus) (DIN 38412)		
	18 mg/l (pimephales promelas) (OECD 203)		
	Dipropylene glycol monomethyl ether		
EC50/48h	1,919 mg/l (daphnia magna)		
EC50/48h	1,919 mg/l (daphnia magna)		
EC50/72h	>969 mg/l (green alge)		
LC50/96h	>1,000 mg/l (piscis)		
	>10,000 mg/l (Pimephales promelas)		
LC50/72h	>150 mg/l (piscis)		
	(Contd. on page 11)		



Page 11/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 10)

Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics

EL50/48h >1,000 mg/l (daphnia magna)
EL50/72h >1,000 mg/l (green alge)
LL50/96h >1,000 mg/l (piscis)
NOELR/21d 1 mg/l (daphnia magna)
NOELR/28d 0.103 mg/l (piscis)

12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

 $\begin{array}{ll} \cdot \ \ \, \underline{\text{12.5 Results of PBT and vPvB assessment}} \\ \cdot \ \ \, \underline{\text{PBT:}} \\ \cdot \ \ \, \text{VPvB:} \end{array} \qquad \begin{array}{ll} \text{Not applicable.} \\ \text{Not applicable.} \end{array}$

12.6 Endocrine disrupting

propertiesThe product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects
 Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous

for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· <u>Recommendation</u> Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1993

14.2 UN proper shipping name

· <u>ADR</u> 1993 FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES)
· <u>IMDG, IATA</u> FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

(Contd. on page 12)



Page 12/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

(Contd. of page 11) 3 · Label IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA Ш 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): · EMS Number: F-E,S-E · Stowage Category · 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

Trade name: PEARL Impregnator

· ADR

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· Transport category · Tunnel restriction code D/E

·IMDG

· Limited quantities (LQ)

Code: E1 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES),

3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation

(EC) No 1272/2008 GHS label elements

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed. P5c FLAMMABLE LIQUIDS Seveso category

· Qualifying quantity (tonnes) for the application of lower-tier

5,000 t requirements

· Qualifying quantity (tonnes) for the

application of upper-tier

50,000 t requirements

(Contd. on page 13)



Page 13/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.09.2022 Version number 12 (replaces version 11) Revision: 06.09.2022

Trade name: PEARL Impregnator

(Contd. of page 12)

REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 738.0 g/l

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory 06.09.2022 · Date of previous version:

· Version number of previous

version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de · Abbreviations and acronyms:

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4